

AUTOMATIC DEVICE PROGRAMMING HANDLER



Automatic Device Programming Handler System
AutoPRO-1203

COPYRIGHT © 2006 COMPASS SYSTEMS INC.,

Automatic Mass Programming Handler System

www.compass21.com
cs@compass21.com

Overview

Low Cost Automatic Type

- Automatic Device Programming Handler
- 700 UPH (Unit Per Hour)
- In/Out : Tray to Tray
- Tray Loding Capacity: 3 JEDEC Tray
- Pick & Place : 2 Head
- Supports Package: TSOP , BGA (option)
- Real-Time Monitoring of Job processing
- Touch Screen (Option)
- 12Gang Programming Module (4Gang*3)
- Manual XY axis Teaching
- Include Industrial Pentium PC

Features

- Separate operation with OFF-LINE Programming except SMD.
- Programming except SMD on idle time.
- Supports low-cost Module Adaptor separately.
- Quick after-service with domestic base technique insurance.
- Master chip and data file operation.
- Easy programming while change source-file.
- Programming algorithm domestic development quickness correspondence.



[Port Description]

AUTOMATIC DEVICE PROGRAMMING HANDLER

Specification

Power

- AC voltage 210~240 VAC.
- Frequency - 50 - 60 Hz

Dimension

- L x W x H - 1095mm x 905mm x 925mm.

Weight

- 350 KG.

Operating Temperature

- 0-40oC(32-105 oF)

Environmental Requirements

- AIR Pressure : 5.5 Bar(80PSI)
- AIR flow : 85 liters/min(3CFM)

Electrical/Power Requirements

- AC voltage 210~240 VAC.
- Frequency - 50 - 60 Hz

Dimension

- L x W x H - 1095mm x 905mm x 925mm.

Weight

- 350 KG

Operating Temperature

- 0-40oC(32-105 oF)



※ High Speed Auto Handler development 10 years know-how accumulation for small, large production.

1 Cycle Time and Quantity Per 1 Hours

Time	Programming Time 30sec		Programming Time 60sec		Programming Time 90sec	
	Cycle(Times)	Device(Quantity)	Cycle(Times)	Device(Quantity)	Cycle(Times)	Device(Quantity)
(4X3)	82,2	700	48,7	585	34,6	416

* The above item alters as Memory.